5 YEAR WARRANTY

ORIGINE FRANCE GARANTIE
BVCert. 6010761

V-INSP-S
Maturing cabinet
Built-in and Flush-fitted – Integrated glass door
1-temperature

Sliding shelf (6 bottles)
ACMSIW / ACMSIB

Wine service area (11 bottles)
ACMSERVW / ACMSERVB

Storage shelf (up to 22 bottles)
AXIHW / AXIHB

Half shelf (5 bottles)
ACMSI-DEMI

CONFIGURATIONS

Premium Pack bottle capacity [1]	Service Pack bottle capacity [1]	Storage Pack bottle capacity [1]
29	28	30
4 sliding shelves (+grid)	2 sliding shelves 1 half shelf 1 Wine service area	1 sliding shelf 1 storage shelf (+grid)

GENERAL FEATURES

	Integrated glass
Gross weight packaged (kg)	61,2
Empty net weight (kg)	52,7
Dimensions H x W x D (mm)	810-880 x 594 x 590
Dimensions packaged H x W x D (mm)	980 x 645 x 630

TECHNICAL FEATURES

REGULATION

- On/Off button
- Electronic regulation
- Temperature setting range between 5°C and 20°C
- Electronic external display and settings
- LED screen
- Backlit capacitive keys
- Visual and/or sound alarms in case of:
  - Temperature dysfunction (sound and visual)
  - Hygrometry dysfunction (visual)
  - Sensor fault (sound and visual)
  - Hygrometry limit (visual)
  - Open door (sound and visual)
  - Need to replace charcoal filter (visual)
- Automatic defrost
- Frost protection thermostat (double protection)

HOT – COLD – INSULATION TECHNOLOGIES

Cold production:	• Static • Compressor R600a
Cords:	• CE/UK/AU/CH/US
Heat production:	• Heating element
Heat release:	• Automatic, adjustable threshold
Inner material:	• Stucco aluminum
Exterior coating material:	• HDF (High Density Fiber) melamine-faced panels
Insulation type:	• Injected polyurethane foam (59mm)

EQUIPEMENT & ACCESSOIRES

EQUIPMENT

- Reversible integrated glass door with soft close and door stop
- Max thickness of the door panel : 20 mm
- Max weight of the door panel: 12 kg
- Inner lighting : light strip and 2 LED (3 options: permanent, open door, disabled)
- Charcoal filter
- 4 adjustable feet
- Humidity cartridge

ACCESSORIES

- Sliding shelves with Mains du Sommelier, open / close locking notch, setting of the Main du Sommelier at the front of the shelf
- 6 removable bottles identifiers per sliding shelf
- 1 erasable felt-tip marker
- 1 microfiber cloth
- 1 EuroCave key ring

ENERGY EFFICIENCY & CONSUMPTION

Cords	230V-50Hz (R600a)
Type of door	Integrated glass
Energy efficiency class	A
Annual energy consumption AEc [2] (Kwh/year)	125
Useful volume (liters)	100
Sound emission (dB(A))	38
Ambient temperature range (°C)	12-35

1. Traditional Bordeaux bottles
2. Calculation based on the result obtained over 24 hrs in standard conditions (25°C / 77°F)