



## S-259V3

Flush fitting wine cabinet  
Multi-temperatures  
Premium pack



Sliding shelf  
ACM5C B

### GENERAL FEATURES

	<b>Full Glass door</b>
Gross weight packaged (kg)*	82
Net weight (kg)*	74
Dimensions H x W x D (mm)	1790 x 595 x 565
Dimensions in pack H x W x D (mm)	1920 x 620 x 620
Colors	Nero - RAL 9005

### TECHNICAL FEATURES

#### REGULATION

- Electronic regulation from 5 to 22°C (5 to 12°C at the bottom and 15 à 22°C at the top)
- Inner electronic display and settings
- LED screen with touch buttons
- Hygrometry and temperature visualisation
- Automatic defrost
- Visual alarms in case of disfunctioning: door open, fault sensor, temperature, carbon filter

#### HOT – COLD – INSULATION TECHNOLOGIES

- |                             |                              |
|-----------------------------|------------------------------|
| Cold production:            | • Static cooling             |
| Cords:                      | • CE/ UK/ AU/ CH             |
| Hot production:             | • Automatic. Heating element |
| Hot release :               | • Threshold : adjustable     |
| Inner material :            | • Aluminium                  |
| Exterior coating material : | • HDF (High Density Fiber)   |
| Insulation type:            | • PU foam                    |



BVCert. 6010761

### EQUIPMENTS & ACCESSORIES

#### EQUIPMENT

- On/ Off button
- Technic or full glass doors
- Inner lighting (3 lighting options: permanent, open door, disabled)
- Charcoal filter (with counter)
- Front adjustable feet
- Lock
- 1 EuroCave key ring

#### ACCESSORIES

- 14 sliding shelves
- Overall capacity: 118 bottles\*\*
- Sliding shelf capacity: 8 bottles

### ENERGY EFFICIENCY AND CONSUMPTION

Wiring	230V-50Hz (gas R600a)	
	Full Glass	Technic
Doors type		
Energy efficiency rating	A	A
Annual energy consumption AEc (Kwh/year)***	157	157
Useful volume (L)	325	325
Acoustic emissions (dB(A))	37	37

\* Empty wine cabinet weight  
\*\* Traditional Bordeaux bottles  
\*\*\* Calculation based on the result obtained over 24 hrs in standard conditions (25°C / 77°F)